



MATERIALS LIST

- A PRESSURE REGULATOR WILKINS 600 HLR SERIES OR EQUAL (WITH INTERNAL BYPASS AND STRAINER)
- B) BRONZE BALL VALVE, THREADED.
- NIPPLE x 2 1/2" LONG, MALE.
- (D) UNION, FEMALE.
- (E) ADAPTER, FEMALE x COMPRESSION FITTING FOR COPPER.
- F METER BOX FOR 1" INSTALLATION:

CARSON INDUSTRIES 1730-18 BCFXL WITH 1730 COVER

FOR 1 1/2" & 2" INSTALLATION:

CARSON INDUSTRIES 1730-18 BCFXL WITH 1730 COVER

FOR ALL SIZE INSTALLATIONS:

PROVIDE CARSON INDUSTRIES DUCTILE IRON COVER IN LANDSCAPING. FOR SIDEWALKS AND AREAS WITH VEHICULAR TRAFFIC, PROVIDE OLYMPIC FOUNDRY SM-30 CAST IRON BOX & COVER.

(G) 1" ROUND WASHED GRAVEL, 8" MIN. DEPTH.

NOTES:

- PRESSURE REGULATOR SIZE AS SPECIFIED OR SHOWN ON PLAN.
- 2. SIZES FOR ITEMS (B) THROUGH (E) SHALL CORRESPOND TO THE SPECIFIED SIZE OF THE PRESSURE REGULATOR.
- 3. ALL FITTINGS AND NIPPLES ARE BRASS WITH IRON PIPE THREADS.



City of Bellevue

WATER UTILITY

TITLE

INDIVIDUAL PRESSURE REDUCING

VALVE ASSEMBLY

(MULTI-FAMILY OR COMMERCIAL) NO. W-21

JANUARY 2017

NO SCALE