



- KIOSK ROOF (BY LAYER):
 - 5/8" ROUGH SAWN FIR PLYWOOD SHEATHING, FACING DOWN, TREATED TO MATCH RAFTERS
 - 3/4" CDX PLYWOOD SHEATHING
 - #15 ROOF FELT UNDERLAYMENT
 - 22 GA. CORE TEN CORRUGATED STEEL ROOFING
 - *NO NAIL PROTRUSIONS THROUGH UNDERSIDE
- 5 1/8"x4 1/2" GLULAM ROOF BEAM
 - CAP ALL EXPOSED BEAMS WITH 20 GA. GALV. STEEL FLASHING
- 4 1/2"x3 1/8" GLULAM RAFTERS
- 6"x3 1/8" GLULAM ANGLED ROOF BRACE, SEE SECTION
- 6"x6 3/4" GLULAM POST
- DISPLAY CASE WITH 2x3 CEDAR FRAME WITH 1/4" CLEAR LEXAN WINDOW SUPPORTED BY 3/4" CDX PLYWOOD BACKING, SEE DISPLAY CASE SECTION
- SIMPSON COLUMN BASE BRACKET, SIZE AS REQUIRED, OR APPROVED EQUAL
 - SECURE BRACKET TO POST WITH (2) EACH 1/2" DIA. CARRIAGE BOLT, NUT AND WASHER, LENGTH AS REQUIRED

- NOTES:**
1. ALL GLULAM MEMBERS TO BE ALASKAN YELLOW CEDAR COMB. 70, ARCHITECTURAL APPEARANCE, NON INCISED.
 2. ALL CEDAR TO BE SELECT TIGHT KNOT WESTERN RED CEDAR OR APPROVED EQUAL.
 3. ALL GLULAM MEMBERS AND CEDAR TO RECEIVE TWO COATS SIKKENS PROLUXE #003 STAIN OR APPROVED EQUAL. STAIN COLOR TO BE DETERMINED BY OWNER.
 4. ALL CONNECTION HARDWARE TO BE HOT DIPPED GALVANIZED.



City of
Bellevue

TITLE:
**COAL CREEK NATURAL AREA - SIGN - 1 OR 2
SIDED KIOSK - FRONT ELEVATION**

DRAWING #:	PK-CC-05A
SCALE:	N.T.S.
REVISION DATE:	02-2022
DEPARTMENT:	PARKS