



- 4x4 CEDAR RAFTERS
- 4x4 CEDAR SUPPORT BEAMS BETWEEN POSTS
-ANCHORED TO POSTS WITH 1/2"x5" CARRIAGE BOLT, NUT AND WASHER, RECESSED 1/2", TYP.
- 4x4 CEDAR ROOF SUPPORT BEAMS BETWEEN RAFTERS
- 4x4 CEDAR ANGLED SUPPORT BRACE AT POSTS
- KIOSK POST: (2) 3x8 CEDAR, SEE POST DETAIL
- DISPLAY CASE WITH 2x3 CEDAR FRAME WITH 1/4" CLEAR LEXAN WINDOW SUPPORTED BY 3/4" CDX PLYWOOD BACKING, SEE DISPLAY CASE PLAN
- USE HALF LAP JOINTS AT FRAME CORNERS, TYP.
- SIMPSON CB-44 COLUMN BASE BRACKET OR APPROVED EQUAL SANDWICHED BETWEEN 3x8 POSTS AND 4x6 BLOCKING, SEE POST DETAIL
-SECURE BRACKET TO POSTS AND BLOCKING WITH (2) EACH 1/2"x8" CARRIAGE BOLT, NUT AND WASHER, RECESSED 1/2", TYP.
- FINISH GRADE
- CONCRETE FOOTING
- 5/8" MINUS CRUSHED GRAVEL COMPACTED TO 95% DENSITY

NOTES:

1. UNLESS OTHERWISE SPECIFIED, ALL WOOD TO BE SELECT TIGHT KNOT WESTERN RED CEDAR OR APPROVED EQUAL.
2. ALL EXPOSED CEDAR AND ROUGH SAWN FIR SHEATHING TO RECEIVE TWO COATS SIKKENS PROLUXE STAIN OR APPROVED EQUAL. STAIN COLOR TO BE DETERMINED BY BELLEVUE PARKS.
3. ALL BOLTS, NAILS, STAPLES AND HARDWARE TO BE HOT DIPPED GALVANIZED.
4. ROOF SHAPE AND MATERIALS MAY VARY TO MATCH EXISTING ON SIGHT BUILDINGS AND STRUCTURES.



**City of
Bellevue**

TITLE:

SIGN - 3 SIDED KIOSK - FRONT ELEVATION

DRAWING #:	PK-SI-19A
SCALE:	N.T.S.
REVISION DATE:	03-2019
DEPARTMENT:	PARKS