



NOTES:

1. SIGNS SHALL MEET ALL REQUIREMENTS AS ESTABLISHED IN THE LATEST EDITION OF THE FEDERAL HIGHWAY ADMINISTRATION'S MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.).
2. SIGN POST SHALL BE 2"x2" SQUARE STEEL POSTS, MIN. 14 GA. WITH 7/16" DIE-PUNCHED KNOCKOUTS ON 1" CENTERS FULL LENGTH ON ALL FOUR SIDES.
3. FOR HARD SURFACE INSTALLATIONS, CORE 4" DIA. HOLE. ANCHOR LENGTH MAY BE DECREASED TO 12".
4. POST SHALL BE ROLLED CARBON SHEET METAL STEEL, SHALL MEET REQUIREMENTS OF ASTM A653 GRADE 50, AND SHALL BE HOT DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A653, G90, STRUCTURAL QUALITY GRADE 50.
5. ANCHOR SHALL HAVE FOUR 7/16" DIA. HOLES, ONE EACH SIDE, 2" FROM TOP END. ANCHOR SHALL MEET REQUIREMENTS OF ASTM A500 GRADE B AND SHALL BE HOT DIPPED GALVANIZED.
6. DRIVE RIVETS TO BE TL3806 3/8" DIA.
7. CORNER BOLTS TO BE TLCB516M
8. SIGN HEIGHT SHALL BE 6' FROM BOTTOM OF LOWER SIGN TO GRADE FOR MULTIPLE SIGNS ON ONE POST.
9. SIGN HEIGHTS SPECIFIED ON THIS DETAIL DO NOT APPLY TO A.D.A. PARKING SIGNS.



TITLE:

SIGN - PARKING LOT - TYPICAL INSTALLATION

DRAWING #:	PK-SI-24
SCALE:	N.T.S.
REVISION DATE:	12-2018
DEPARTMENT:	PARKS